





# 10MD26 | Mid-Bass

700 W continuous program power capacity  
76 mm (3 in) aluminium voice coil  
80 – 4000 Hz response  
100 dB sensitivity



Horns  
HF Drivers  
Coaxials  
LF Nd Drivers  
LF Drivers

## Specification

Nominal Diameter	250 (10) mm (in)
Nominal Impedance (1)	8 Ohm
Minimum Impedance	7.2 Ohm
Nominal Power Handling (2)	350 W
Continuous Power Handling (3)	700 W
Sensitivity (1W/1m) (4)	100 dB
Frequency Range	80 - 4000 Hz
Voice Coil Diameter	76 (3) mm (in)
Winding Material	Aluminium
Former Material	Glass Fibre
Winding Depth	11 (7/16) mm (in)
Magnetic Gap Depth	8 (5/16) mm (in)
Flux Density	1.45 T

## Thiele & Small Parameters

Fs	76 Hz
Re	5.8 Ohm
Qes	0.22
Qms	4.8
Qts	0.21
Vas	20 (0.71) dm3 (ft3)
Sd	320 (49.1) cm2 (in2)
Eta Zero	3.9 %
Xmax	+/- 1.5 mm
Xvar	+/- 4.5 mm
Mms	31 g
Bl	19.6 Txm
Le	1.2 mH

## Mounting and Shipping Info

Overall Diameter	262 mm (10.3 in)
Bolt Circle Diameter	245 mm (9.6 in)
Baffle Cutout Diameter	230 mm (8.8 in)
Depth	124 mm (4.9 in)
Flange and Gasket Thickness	14 mm (0.55 in)
Net Weight	7.3 kg (16.1 lb)
Shipping Weight	7.9 kg (7.4 lb)
Shipping Box	320x320x160 mm (12x12x6.3 in)

- <sup>1</sup>For different impedances, please ask.
- <sup>2</sup>2 hours test made with continuous pink noise signal (6 dB crest factor). Power calculated on rated minimum impedance.
- <sup>3</sup>Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
- <sup>4</sup>Applied RMS Voltage is set to 2.83V for 8 ohms Nominal Impedance.

