


FTR15-4080HDX



- Glass loaded paper cone with weather-resistant impregnation
- Optimised double suspension
- Airflow vented magnet assembly for dynamic heat dispersion

8 Frequency Response



1. Tested for two hours using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance. Loudspeaker tested in free air.
2. Continuous Power Rating is defined as 3dB greater than the AES rating.
3. Measured on axis at 1W, 1m in 2^l anechoic environment.
4. Xmax derived from: (voice coil winding width-gap depth)/2.
5. Small signal parameters measured after unit subjected to pre-conditioning signal.

General Specifications

Nominal diameter	381mm/15in
Power rating ¹	1000Wrms
Continuous power rating ²	2000W
Nominal impedance	8
Sensitivity ³	96dB
Frequency range	40-2,500Hz
Voice coil diameter	100mm/4in
Chassis type	Cast aluminium
Magnet type	Ferrite
Magnet weight	3.1kg/110oz
Coil material	Round copper
Former material	Glass fibre
Cone material	Glass loaded paper with weather-resistant impregnation
Surround material	Cloth-sealed
Suspension	Double
Xmax ⁴	8mm/0.33in
Gap depth	9.5mm/0.37in
Voice coil winding width	25mm/0.99in

Small Signal Parameters ⁵

D	0.33m/12.99in
Fs	40.Hz
Mms	147.45g/5.2oz
Qms	3.089
Qes	0.357
Mmd	139.38g/4.92oz
Qts	0.320
Re	5.12
Vas	111.2lt3.93ft3
Bl	23.07Tm
Cms	0.11mm/N
Rms	13.77kg/s
Le (at 1kHz)	1.73mH

Mounting Information

Overall diameter	385mm/15.16in
Overall depth	180mm/7.1in
Cut-out diameter	351mm/13.82in
Mounting slot dimensions	10mm x 7mm/0.39in x 0.27in
Number of mounting slots	8
Mounting PCD range	365-375mm/14.37-14.76in
Unit weight	9.7kg/21.4lb

Packed Dimensions & Weight

Single pack size W x D x H	435mm x 435mm x 200mm /17.1in x 17.1in x 7.9in
Single pack weight	11.5kg/25.4lb
Multi pack size W x D x H	1210mmx1050mmx980mm /47.6inx41.3inx35.4in
Multi pack weight	380kg/835lb