

NEODYMIUM

HF104

1" - 40 W - 108 dB

NOMINAL SPECIFICATIONS

Throat Diameter	25.4 mm (1 in)
Overall Diameter	91 mm (3.58 in)
90° Mounting Holes Diameter (4xM6)	77.5 mm (3.05 in)
Depth	51 mm (2.01 in)
Net Weight	850 g (1.87 lb)
Shipping Box	98 x 90 x 64 mm
(Single Carton Box)	(3.86 x 3.54 x 2.52 in)
Shipping Weight	880 g (1.94 lb)

TECHNICAL PARAMETERS

Nominal Impedance	8 Ω
Minimum Impedance	6.9 Ω
AES Power Handling (1)	40 W
Maximum Power Handling (2)	80 W
Minimum Crossover Frequency (3)	1.7 kHz
Sensitivity (1W/1m) (4)	108 dB
Frequency Range	0.8÷20 kHz
Voice Coil Diameter	37 mm (1.46 in)
Winding Material	Al
Former Material	Kapton
Diaphragm Material	Ketone Polymer
Diaphragm Shape	Annular
Winding Depth	2.1 mm (0.08 in)
Magnetic Gap Depth	2.6 mm (0.10 in)
Flux Density	1.85 T
Re	5.5 Ω
Phase Plug Design	Radial

NOTE: Driver Mounted on a 1" 50° X 40° Al horn

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3 dB greater than nominal power.

(3) 12 dB/oct or higher slope high-pass filter.

(4) Averaged within the frequency range.

PATENT PENDING

